



ADELAIDE COLUMN

TYPE LED COLUMN

PROJECT N/A

ZUMA LIGHTING LLC



ORDERING INFORMATION

Model ADELAIDE COLUMN

Type LED COLUMN

PROJECT N/A

FIXTURE	SIZE	SOURCE	VOLTS	LAMP / TEMP	OPTICS	COLOR	OPTIONS
ADE-C = Adelaide Column - Aluminum Construction (LED)	6108 = 6" dia. X 108" H (9ft) 6144 = 6" dia. X 144"H (12ft) 8108 = 8" dia. X 108" H (9ft) 8144 = 8" dia. X 144"H (12ft) CH = Custom height, consult factory*	10W 20W 30W 40W 60W	U = 120v- 277v 8 = 480v	27K = 2700K 3K = 3000K 35K = 3500K 4K = 4000K 5K = 5000K	180° 360°	DB = Dark Bronze BK = Black WH = White SL = Silver CC = Custom	SP = Surge Protection SLED= Static Color LED* CLED = Color Changing LED* PS180 = Perforated Screen 180° (over lens) PS360 = Perforated Screen 360° (over lens) CS = 180° Cutoff Shield GFIP = GFI (Provision Only) *Consult factory for color LED options



SPECIFICATIONS

Housing


Housing is fabricated from 6" extruded aluminum alloy.

LED

High performance LEDs utilize state-of-the-art technologies for improved thermal performance. Available in 180° or 360° distribution with wide choice of color temperatures ranging from CCT(2700K – 6500K).

Lens & Perforated Screen

Lens is fabricated from white frosted acrylic. Available with optional perforated metal screen over lens. Perforated screen can be specified with 360° or 180° pattern. See below for screen options. Additional options available. Consult factory for details.



Mounting Options

Heavy duty base plate secures to the housing. Mounting kit with anchor bolts, included.

Finish

Bollard can be offered with polished stainless steel finish or can be powder coated with any standard color. Custom colors are available upon request.

Certificates & Warranty

- Suitable for Wet Locations
- 5-Year Warranty

