



ZUMALIGHTING
QUALITY OUTDOOR SOLUTIONS



MODEL
AVATANKA

TYPE
LED

SERIES
ARCHITECTURAL

ZUMA LIGHTING LLC
325 N LARCHMONT BLVD STE 406, LOS ANGELES, CA 90004
INFO@ZUMALIGHTING.COM • (310) 975-3126 • ZUMALIGHTING.COM

ORDERING INFORMATION

Model AVATANKA

Type LED

Series ARCHITECTURAL



Avatanka w/ no lens and 4 vertical bars



Avatanka w/ opal white acrylic lens and 2 vertical bars (standard)

FIXTURE	WATTAGE	VOLTS	COLOR TEMP	OPTICS	MOUNT	LENS	COLOR	OPTIONS
AVA	23W = 2300lm - 2700lm 34W = 3450lm - 3900lm 40W = 4180lm - 4620lm 50W = 5300lm - 5750lm 62W = 6500lm - 7100lm 80W = 8350lm to 9150lm <i>Contact sales for additional options</i>	U = 120v-277v 8 = 480v	27K = 2700K 3K = 3000K 4K = 4000K 5K = 5000K	T3 = 180° T5 = 360°	SF238 = Fits over 2- 3/8"OD tenon SF300 = Fits over 3"OD tenon WM = Wall Mount	CA = Clear Acrylic FA = Frosted Acrylic OA = Opal White Acrylic NL = No Lens	BZ8 = Zuma Bronze BK = GT Black WH = Alpine White SL = Iridium Silver GRY = Granite Gray GRN = Moss Green CC = Custom <i>Specify RAL</i>	M = Motion Sensor PC = Photocell D = Dimming S = Surge Protection LS = 180° Cutoff Shield 2S = Double Shade 4VB = 4 Vertical Bars BAA = Buy American Act Compliant DSC = Dark Sky Compliant* <i>*Only available with select optics, contact factory for details</i>

ZUMA LIGHTING LLC

325 N LARCHMONT BLVD STE 406, LOS ANGELES, CA 90004

INFO@ZUMALIGHTING.COM • (310) 975-3126 • ZUMALIGHTING.COM

SPECIFICATIONS

Housing

The fixture housing is constructed from a combination of fabricated and spun aluminum. Shade and optional double shade are fabricated from spun aluminum.

Lens

Acrylic lens available in clear, frosted, and opal white.

Optics

Stacked, spun, and polished louvers – Type III or V

Electrical Components

High performance LEDs utilize state-of-the-art technologies for improved thermal performance. Available in Types II, III, IV, & V with wide choice of color temperatures ranging from CCT(2700K – 6500K). These LEDs are designed to fit LEDIL lenses with IP67 rating.

Finish

Thermoset polyester oven-baked powder coat, in any standard color. Custom colors are available to your specification.

Certificates & Warranty

- ETL Listed
- Suitable for Wet Locations
- 5-Year Warranty

Mounting

Fixture can be installed on post-top.

Tenon top mounting options:

- over 3" OD (standard)
- over 2-3/8" OD

Fixture can also be installed on mounting arms, sold separately. See architectural arm .pdf for style options.

